

QuickSee Free

Accurate autorefraction anywhere



Desktop power in a handheld

4

Fast

Accurate measurements in 10 seconds



Easy to use

Modern and intuitive design



QuickSee Free's combination of the open view design, wavefront aberrometry, and dynamic measurements produces clinically accurate autorefraction measurements, in a durable handheld format suitable for use in your practice and in the field.

The patented PlenOptika Wavefront Refraction Engine™ performs continuous data analysis, making QuickSee Free as accurate as the high-end clinical desktop autorefractors and demonstrating excellent agreement with subjective refraction.

QuickSee Free's technology has been clinically-evaluated in five IRB-based studies and documented in seven peer-reviewed publications and conference abstracts. QuickSee Free has FDA Class I 510(k) exempt medical device registration.



QuickSee Free's design and UI are modern and friendly

QuickSee Free



Video view for fast cameraaided alignment



Dynamic measurements captured in less than 10 seconds



>10,000 results storage; Bluetooth printer compatible and data exportable through Companion app



Intuitive, modern interface design in 15 languages

Technical specifications

| Pupil size | 2 to 8 mm |
|--|--|
| Intended patient population | >= 3 years |
| Accommodation control | Open view, Fogging lens (optional) |
| Cycloplegia requirement | None |
| Contact lens wearers (excluding multifocal lenses) | Over-refraction compatible |
| Dilation Requirement | None |
| Illumination requirements | None |
| Acquisition time | 10 seconds |
| Spherical Range | -12D to +10D, increments of 0.01D, 0.125D, 0.25D |
| Cylindrical Range | -8D to +8D, increments of 0.01D, 0.125D, 0.25D |
| Axial range | 0–180°, increments of 1°, 5°, 10° |
| Base Technology | Wavefront aberrometry |

General specifications

| Display properties | 2.4-inch LCD, capacitive touch screen, readable outdoors, true color (65,536 colors) |
|--|--|
| Charger properties | USB-C medical grade wall adapter, AC 100 to 240V, 50/60 Hz |
| Battery | 6 hours continuous use +/– 1 hour (10,000 mAh Li-ion); 5 hours charge time; IEC 62133-2:2017 certified |
| Calibration | Factory calibrated; no field calibration needed |
| Measurement capacity | Measurement storage capacity: > 10,000 measurements |
| Regulatory classification (medical device) | Class I FDA (USA), Class IIa Product CE, MDR Compliant, Class IIa, UKCA, MDR 2002 Compliant |
| Laser safety | Class 1, IEC 60825-1:2014 certified |
| Weight | < 750 grams / 1.65 lbs |
| Dimensions | 30 cm (H) x 5.5 cm (W), 18 cm (L) |



QuickSee Companion App

for results download, available for Android and Windows OS



Bluetooth printer included

pre-paired with QuickSee Free for easy results printing



PlenOptika Europe, S.L.U. Parque Científico de Madrid Calle Faraday 7, #2.06 Madrid, 28049 Spain

plenoptika.com @plenoptika LinkedIn / Instagram / Facebook